

HPI 33 EVO

Three Phase UPS
10 - 40 kW



GLOBAL SPECIALIST IN ELECTRICAL
AND DIGITAL BUILDING INFRASTRUCTURES



SUSTAINABILITY

Corporate Social Responsibility

Green management and sustainable supply chain: these concepts are part of Legrand's Corporate Social Responsibility, which is the company's commitment to drawing up a strategy and implementing it with practical actions aimed at socially responsible behaviour towards everything around it, such as people, things and environment.

CSR involves the management of human resources, the organization and division of labour and the management of natural resources. CSR aims to assess the impact that the company's actions and decisions have internally, but also externally, on the stakeholders and the environment.

BUSINESS ECOSYSTEM


or how Legrand interacts ethically with the whole ecosystem of its activities.

PEOPLE

or how Legrand engages with all of its employees and stakeholders.

ENVIRONMENT

or how Legrand intends to limit the Group's environmental impact.



Circular economy

We are committed to creating a system that involves all stakeholders to share values, objectives and actions in order to control and reduce the environmental impact of all our economic and production processes, reduce waste and environmental impact and transform what would once have been defined as «waste» into new resources. Controlling these aspects has an impact on the entire life cycle of the product, starting from the design of new concepts and new specifications for the materials the UPS is made of; this is possible through responsible design and procurement processes (so-called «green procurement»), with a strong focus on research and the use of innovative materials from the circular economy and alternative raw materials. When a product ends its life, all these materials can become high value-added resources that can be used in other production cycles.



Digitalization

New information technologies allow us to reduce the use of several paper documents in favor of the digital format: in this way the information is always and everywhere accessible from a PC or smartphone and at the same time we can avoid the felling of many trees.

Digitization also becomes an important driver of the circular economy, since it allows the use of tools for performance data analysis and preventive diagnostics, both useful for optimizing the life cycle and durability of the product.



Efficiency

Our R&D team is constantly working on the development of increasingly efficient UPSs that allow high and incremental performance with minimum energy dissipation; with regard to CO₂ emissions, we are implementing processes and products that represent an improvement in the percentage of carbon footprint compared to the past.

But efficiency is not only synonymous with high performance.

For us, efficiency also means ecodesign: this implies that the UPS is designed to be easily repaired, maintained and it's easy to separate its components.

This means increasing the durability of our UPSs and the possibility of reusing and recycling them at the end of their life.



L'EPD/PEP

For each product family we draw up an EPD (Environmental Product Declaration) or PEP (Profil Environnemental Produit) in line with ISO 14025: it is a declaration that is a sort of environmental photograph of the product.

The EPD is drawn up according to the concept of Life Cycle Assessment: it examines the environmental impact of a product throughout its life cycle, from the development of product specifications to the choice of materials to be used and the end-of-life destination of the product itself.



HPi 33 EVO

Three Phase UPS
10 - 40 kW

THE EVOLUTION IS HERE

At Legrand, we have always been driven by need-based innovations and smart solutions that addresses the changing needs of our customers. Our all new HPi 33 EVO is the result of this constant drive to offer you the best solutions with respect to maximum power availability, reliability and high efficiency.

HPi 33 EVO is a true online double conversion UPS with APFC PWM IGBT based design that delivers unity output power factor. It supplies a rated output power of 10-40 kW with kVA = kW. With up to 95% efficiency, HPi 33 EVO helps users have lowest total cost of ownership. HPi 33 EVO offers a seamless power protection solution and is ideally suited for mission critical applications in IT, ITeS, infrastructure, education, manufacturing, healthcare, small and medium data centers.




Evolution In **PERFORMANCE**


HPi 33 EVO is designed to provide a true evolution in high performance. It comes with an IGBT rectifier and inverter which delivers quality and efficient power output, making it an ideal choice for your mission critical applications. The power architecture is designed to offer maximum active power, up to 95% efficiency and a low THDi. The intelligent fan operation ensures optimal cooling by automatically regulating the temperature resulting in reduced operational costs and high efficiency levels.




**Unity
Power Factor**



**Low
Harmonics**



**Up to
95% Efficiency**





Optimal Cooling



IGBT Rectifier

Evolution In **EASE OF USE**

The 5" intuitive display is extremely user-friendly and helps in monitoring various system parameters like I/O voltage, battery parameters, output power/load PF, mimic power flow diagram, and history logs with ease. Designed to use up to 30% less space, the HPI 33 EVO has a compact footprint, results in significant reduction in real estate costs. It is also equipped with a wide range of external monitoring options like Simple Network Management Protocol (SNMP), Modbus, RS 232 and USB etc., which enables a user to remotely manage the UPS. These aspects of HPI 33 EVO represent an evolution in ease of use and contribute to its overall functionality.






**Compact
Footprint**




**Network
Management
Options**




Evolution In **FLEXIBILITY**


HPi 33 EVO allows N+X redundancy up to 4 UPSs in parallel operation, effectively reducing the risk of downtime. Additionally, it can be scaled up to 2 units in parallel with a common battery configuration to achieve increased reliability, efficient load sharing and highest power availability. Evolution in flexibility is also achieved by an advanced battery management function which enables users to optimize the performance and lifespan of the battery system. A flexible DC Bus provides a wide battery operating window and enables scalability of the system. The HPi 33 EVO also offers an optional isolation transformer that safeguards critical equipment from unconditioned input power and enables its safe operation.



N+X Redundancy



**Common Battery
Configuration**



**Isolation
Transformer**



Advanced Battery Management



Temperature Compensated Battery Charger



Selectable & Adjustable Battery Charging Current



Flexible DC Bus

Evolution In **PROTECTION**

When it comes to evolution in protection, the HPi 33 EVO scores on several fronts. The UPS is equipped with a dust filter which helps in protecting the UPS from dust particles.

A wide input voltage window enables it to operate within a broad range of input voltages, ensuring reliable performance and protection of connected equipment. The conformal coated PCBs provide protection against environmental factors, preventing corrosion and electrical failures, thereby increasing the reliability and longevity of the UPS. A built in phase reversal protection and correction system along with built in input, output and MBS switches ensure added protection to the equipment.



**Phase Reversal
Correction**



**Wide Input
Voltage Window**



Dust Filter





**Built-in Input,
Output And
MBS Switches**



**Conformal
Coated Boards**



HPI 33 EVO 10 - 40 kW

Three Phase UPS

PID No.	311400	311401	311402	311403
Rating	10 kVA	20 kVA	30 kVA	40 kVA
General Characteristics				
Nominal power (kVA)	10 kVA	20 kVA	30 kVA	40 kVA
Active power (kW)*	10 kW	20 kW	30 kW	40 kW
Technology	Online double conversion VFI-SS-111			
Waveform	Pure sinewave			
Architecture	Monolithic UPS paralleleable upto 4 units			
Input Characteristics				
Input voltage	380/400/415 VAC - 3PH + N + Earth			
Input frequency	45 - 55 Hz			
Input voltage range	320 VAC - 476 VAC			
Input THDi	< 4% @ Rated linear load	< 3% @ Rated linear load		
Input PF	> 0.99 @ Rated linear load			
Output Characteristics				
Output voltage	400 VAC +/- 1% 3-Ph + N + E (Settable to 380/400/415 VAC)			
Efficiency in double conversion mode	Upto 93%	Upto 94%		Upto 95%
Output frequency (nominal)	50 Hz/60 Hz			
Crest factor	3:1			
Overload capacity at online mode	Upto 110% for 1 hour, 125% for 10 min & 150% for 1 min			
Overload capacity at bypass mode	Upto 110% continuous & > 150% for 10 ms			
Efficiency in ECO mode	> 98%			
Isolation transformer	Optional, Integrated			
Battery Characteristics				
Battery type	VRLA, LiB			
Internal/External batteries	External			
Battery nominal VDC	240 VDC		480 VDC	
Common battery configuration	Yes upto 2 UPS's			
Communication and Management				
Display	5" Touch screen LCD display to monitor UPS status in real time			
Communication port	RS232, RS485, Relay contact			
Network interface	Optional with SNMP			
REPO	Yes			
Alarms & Signals	All the required alarms & signals			
Physical Characteristics				
Unit dimensions (W x H X D)	250 x 660 x 590 in mm			
Unit net weight	50 Kgs			
Environmental Characteristics				
Operating temperature	0-40°C			
Degree of protection	IP20			
Relative humidity(%)	0-95% (non condensing)			
Noise level at 1m (dbA)	Max 65 dbA at 100% load			
Standards & Certifications				
Safety	IEC 62040-1			
EMC	IEC 62040-2			
Performance & testing	IEC 62040-3			
Other	CE, RoHS			

*at 35 degree celsius.
General tolerance +/- 2mm
Note: Product specifications are subject to change due to continous development. Please ask for confirmation given in the publication.



CUSTOMER SERVICES



Reliable

Directly present in more than 70 countries and servicing its products in more than 150 countries worldwide, a team of qualified engineers is available to support your UPS system to ensure power quality and availability to the most critical loads.

Excellent

Legrand's competitive edge lies in its ability to provide high value-added UPS systems and services for both end users and business partners. For Legrand, creating value means coming up with solutions for lower energy consumption, but also integrating product design into the overall development process. With around 200 000 catalogue items, the Group also provides all products required for electrical and digital building installations, particularly as integrated systems, finding solutions to fit everyone's needs.

Tailor-made

Legrand offers a complete range of specific solutions and services to meet customer requirements:

- Technical pre-sales support at the project design stage
- Factory acceptance test
- Supervision of installation, testing and commissioning, site acceptance test
- Operator training
- Site audit
- Warranty extension
- Annual maintenance contract
- Fast intervention on emergency call

SERVICE

SUPPORT



SITE INSPECTION, INSTALLATION SUPERVISION.

We perform a comprehensive check of the UPS environment to ensure safety and fault-free operation.

Our technical experts give manufacturer's recommendations to the site engineer or electrical contractors, and supervise the UPS installation before load power-up.

SITE TEST, COMMISSIONING.

Our Service Engineers conduct rigorous site tests and full setting-up of the UPS system before going live. They also perform site acceptance tests according to your requirements. Commissioning operations for all UPS are carried out by qualified engineers to guarantee seamless start-up. After the final handing over of the UPS system, a Test and Commissioning report is delivered to you.

TRAINING



We offer on-site training to ensure your equipment's safe and efficient operation.

Troubleshooting courses are also available in our plants for intensive hands-on practice on UPS training equipment.

MAINTENANCE



PREVENTIVE MAINTENANCE

Electronic equipment and power systems, such as UPS, contain life-limited components and parts that must be replaced according to the manufacturer's specifications.

To ensure optimal performance and to protect your critical application from potential downtime, it is crucial to perform

preventive maintenance operations on a regular basis and replace parts when needed. Our Service Contracts include cleaning, IR thermography, measurements, functional tests, event log and power quality analysis, battery health check, hardware and software upgrades, and technical reports. A Preventive Maintenance Plan is one of the most cost-effective actions that can preserve your initial investment and ensure your business continuity.

CORRECTIVE MAINTENANCE, EMERGENCY CALL

In the event of an Emergency Call, our worldwide service network, with engineers and spare-parts stocks strategically located as close as possible to your site, guarantees a fast intervention time with 24/7/365 assistance.

After connecting his laptop to your UPS, very powerful diagnostic software helps our engineer to identify the fault, thus ensuring short MTTR (Mean Time To Repair).

Corrective actions are performed such as part replacement, adjustments and upgrades to return the UPS system back to normal operation.

[illegible]

Head Office

10th Floor, Prestige Center Court,
Office Block, Vijaya Forum Mall, 183,
N.S.K Salai, Vadapalani,
Chennai - 600 026.
Phone: +91 44 4656 5555

Regional Offices

New Delhi

B-225, Okhla Industrial Area,
4th Floor, Phase-1,
New Delhi - 110 020.
Phone: +91 11 2699 0028

Kolkata

Bhakta Tower, Plot No. KB22,
2nd & 3rd Floor, Salt Lake City,
Sector - III, Kolkata - 700 098.
Phone : +91 33 4021 3535 / 3536

Mumbai

C/203, Corporate Avenue, Atul Projects,
Near Mirador Hotel, Chakala,
Andheri Ghatkopar Link Road,
Andheri (East), Mumbai - 400 099.
Phone : +91 22 3385 6201

Chennai

10th Floor, Prestige Center Court,
Office Block, Vijaya Forum Mall,
183, N.S.K Salai, Vadapalani,
Chennai - 600 026.
Phone : +91 44 3024 7236 / 200

Branch Offices

Chandigarh

SCO 4, First Floor, Sector 16,
Panchkula, Chandigarh - 134 109.
Phone : +91 93160 06215

Dehradun

Unit-1 and 2, Chakrata Road,
Vijay Park Dehradun - 248001.
Uttarakhand
Phone : +91 135 661 6111

Jaipur

Plot No. J-6, Scheme-12B,
Sharma Colony, Bais Godown,
Jaipur - 302 019.
Phone : +91 141 221 9082

Lucknow

209/B, 2nd Floor, Cyber Heights,
Vibhuti Khand, Gomti Nagar,
Lucknow - 226 018.
Phone : +91 93352 01364

Bhubaneswar

N-2/72 Ground Floor, IRC Village,
Nayapally, Bhubaneswar - 751 015.
Phone: +91 674 255 0760

Guwahati

House No 02,
Rajgarh Girls High School Road
(Behind Rajgarh Girls High School),
Guwahati - 781 007.
Phone : +91 96000 87171

Patna

405, Fraser Road, Hemplaza,
4th Floor, Patna - 800 001.
Phone : +91 612 220 0657

Ranchi

202 & 203, 2nd Floor, Sunrise Forum,
Bardwan Compound, Lalpur, 2nd Floor,
Ranchi - 834 001.
Phone : + 91 98300 62078

Ahmedabad

A-101/102, Mondeal Heights,
Beside Hotel Novotel, Near Iscon Circle,
S G Highway, Ahmedabad - 380 015.
Phone : +91 79 6134 0555

Bhopal

Plot No. 2, 221, 2nd Floor, Akansha Complex,
Zone-1, M.P.Nagar, Bhopal- 462 011.
Phone : +91 755 276 4202

Nagpur

Plot.No.174, H.No.4181/C/174, 1st Floor,
Loksewa Housing Society, Near Dr. Umathe
& Mokhare College, Bhamti Road,
Loksewa Nagar, Nagpur - 440 022.
Phone : +91 712 228 6991 / 228 9668

Pune

Pinacle 664 park avenue, 8th floor,
Plot no 102+103, CTS No. 66/4,
Final, 4, Law College Rd, Erandwane,
Pune, Maharashtra - 411 004.
Phone : +91 +20 6729 5624

Bengaluru

No-58, First Floor, Firoze White Manor,
Bowring Hospital Road,
Shivajinagar, Bangalore -560 001.
Phone : +91 80 6822 0000

Coimbatore

No. B-15, Thirumalai Towers, No. 723,
1st Floor, Avinashi Road, Coimbatore - 641 018.
Phone : +91 422 420 4018

Hyderabad

Prestige Phoenix Building,
1st Floor, Survey no. 199,
No. 6-3-1219/J/101 & 102, Uma Nagar,
Opposite to Begumpet Metro Station
Begumpet 500016
Phone : +91 40 4567 1717/2341 4398/2341 4367

Kochi

Door No. 50/1107A9, JB Manjooran Estate,
3rd Floor, Bypass Junction,
Edappally, Kochi - 682 024.
Phone : +91 484 6604 710

Madurai

12/2, DSP Nagar,
Dinamalar Avenue,
Madurai - 625 016.
Phone : +91 452 260 4555

NUMERIC®

A Group brand |  **legrand®**

Contact us.:

Email : customer.care@numericups.com

Phone : 0484-3103266 / 4723266

www.numericups.com